



Since 1946
tractor is zetor

Zetor



PROXIMA PLUS

Z 8541 • Z 9541 • Z 10541

www.zetor.com

ZETOR PROXIMA PLUS SPECIFICATIONS

MODEL	Z 8541	Z 9541	Z 10541
ENGINE			
Model	Zetor 1204	Zetor 1004	Zetor 1304
Power (kW/HP) ECE R24	60/82	66/90	74/100
Rated speed (rpm)	2200		
No. of cylinders	4		
Aspiration	turbocharged		
Bore/Stroke (mm)	105/120		
Displacement (cc)	4156		
Torque reserve (%)	35		
Emissions	TIER II		
CLUTCH			
Type	dry, single plate, hydraulic control		
Diameter (mm)	310		
Lining	cerametallic		
TRANSMISSION			
Type	two-stage power shift, mechanical		
Shifting	fully synchronised		
Gears forward/reverse	16/16		
Speed (kmph)	30 and 40	40	
PTO SHAFT			
Type	live/ground speed, wet multi-plate PTO clutch		
Speeds (rpm)	540/1000 (540/540E)		
Front PTO - speed	+1000 (-1000)		
HYDRAULICS			
Type	mechanical, top link draft sensing		
Three point linkage	category I and II		
Control	position, draft, mixed		
Lift capacity (kN)	41.5		
Operating pressure (MPa)	18		
Pump capacity (l/min)	50		
SCV's	three set of remotes standard		
OTHER			
Drive system	4WD		
Operator's station	cab version		
Steering	hydrostatic		
Service brake	wet disc brake, hydraulic control		
Parking brake	mechanical control		
Front axle 4WD	Carraro 20.16, wet brakes in wheels		
Rear axle	differential lock engaged electro-pneumatically		
DIMENSIONS			
Maximum length (mm)	4324		
Maximum width (mm)	1910		
Maximum height (mm)	2692		
Wheel base (mm)	2328		
Ground clearance (mm)	402		
Standard front tyres	11.2-24		
Standard rear tyres	16.9-30		
Weight (kg)	4010		
OPTIONAL			
	adjustable steering wheel; A/C		
	adjustable trailer hitch; pick-up hitch; front three point hitch		
	front and rear weights; block heater; mate's seat		
	hydraulic or air pressure trailer brakes		
	choice of tyre combinations		



Zetor Trade, s. r. o.
 Trnkova 111, 632 00 Brno
 Czech Republic
 www.zetor.com

DISTRIBUTED BY: